



Armour Fire Safety

Features: B C Purple K Dry Chemical

For high hazard Class B and C fires

Badger's potassium bicarbonate Purple K dry chemical stored pressure fire extinguishers are designed for use on high hazard types of Class B and C fires.

Purple K is generally superior to other dry chemicals on Class B fires, making these extinguishers ideal for use in industrial and commercial premises where a flammable liquid or gas fire risks exist. The extinguishers can be mounted on any flat vertical surface with a wall hook or supplied with an optional strap bracket.










For special fire hazard protection consider the CR Corrosion Resistant model.



A UTC Fire & Security Company



Features

-  Chrome plated brass valve
-  Stainless steel handle, lever and hose band
-  Steel cylinder and internal siphon tube
-  Six year warranty
-  Large loop stainless steel pull pins with tether
-  12 year periodic hydrostatic test interval
-  Heavy-duty hose with plated brass hex fitting
-  ULC Listed and USCG Approved
-  Easy-to-read two-piece nameplates



Armour Fire Safety

Customer Service | Teamwork | Trust & Integrity | Reputation | Performance





Armour Fire Safety

Features: B C Purple K Dry Chemical

Technical Data:

BADGER Extra Purple K Dry Chemical Stored Pressure Extinguishers

MODEL	B10P	B20P
PART NUMBER	24191	24194
CAPACITY (lb.)	10	20
CAPACITY (kg)	4.5	9.1
ULC FIRE RATING	30-B:C	120-B:C
AGENT TYPE	Purple K	Purple K
CYLINDER MATERIAL	Steel	Steel
VALVE MATERIAL	Plated Brass	Plated Brass
HANDLE/LEVER MATERIAL	Stainless Steel	Stainless Steel
EXPELLANT	Nitrogen	Nitrogen
Operating Pressure @ 70° F	195	195
TEMPERATURE RANGE (° F)	-40 to 120	-40 to 120
TEMPERATURE RANGE (° C)	-40.0 to 48.9	-40.0 to 48.9
AGENT FLOW RATE (lb/sec)	0.45	0.71
AGENT FLOW RATE (kg/sec)	0.20	0.32
NOM. DISCHARGE TIME (sec)	22	28
DISCHARGE RANGE (ft.)	16.0 to 20.0	25.0 to 30.0
DISCHARGE RANGE (m)	4.9 to 6.1	7.6 to 9.1
UNIT HEIGHT (in.)	18.94	21.13
UNIT HEIGHT (cm)	48.1	53.7
UNIT WIDTH (in.)	7.75	9.25
UNIT WIDTH (cm)	19.7	23.5
UNIT DEPTH (in.)	5.25	7.25
UNIT DEPTH (cm)	13.3	18.4
SHIPPING WEIGHT (lb.)	17	32
SHIPPING WEIGHT (kg)	7.7	14.5
USCG APPROVAL	Type B:C Size-II	Type B:C Size-III
BRACKET	UB-10 Optional	UB-20 Optional

This information is subject to change without notice. Kidde Canada Inc. disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Kidde Canada Inc. for your local distributor for assistance.

